

All HTML Elements		15
accessKey	addBehavior("URL") W5	onActivate IE5.5
all[]	applyElement(elem[,type]) W5	onBeforeCopy W5
behaviorUrns[] W5	attachEvent("evt",func) W5	onBeforeCut W5
canHaveChildren W5	blur()	onBeforeDeactivate IE5.5
canHaveHTML IE5.5	clearAttributes() W5	onBeforeEditFocus W5
children	click()	onBeforePaste W5
className	componentFromPoint(x,y) W5	onBlur
clientHeight	contains(elem) W5	onClick
clientLeft	detachEvent("evt",func) W5	onContextMenu W5
clientTop	fireEvent("evt",[,ev]) IE5.5	onControlSelect IE5.5
clientWidth	focus()	onCopy W5
contentEditable IE5.5	getAdjacentText() W5	onCut W5
currentStyle IE5	getAttribute("attr",[,case]) W5	onDblClick
dataFld W4	getBoundingClientRect() W5	onDeactivate IE5.5
dataFormatAs W4	getClientRects() W5	onDrag W5
dataSrc W4	getExpression() W5	onDragEnd W5
disabled	insertAdjacentElement() W5	onDragEnter W5
document	insertAdjacentHTML()	onDragLeave W5
filters[] W4	insertAdjacentText()	onDragOver W5
hideFocus IE5.5	item(index[,subindex]) (1)	onDragStart W5
id	mergeAttributes() W5	onDrop W5
innerHTML	releaseCapture() W5	onFilterChange W4
innerText	removeAttribute("attr",[,case])	onFocus
isContentEditable	removeBehavior() (ID) W5	onHelp W4, W5
isDisabled IE5.5	removeExpression("prop") W5	onKeyDown
isMultiline IE5.5	removeNode(children) W5	onKeyPress
isTextEdit W4	replaceAdjacentText("loc", "txt") W5	onKeyUp
lang	replaceNode(new) W5	onLoseCapture W5
language	scrollIntoView(top)	onMouseDown
length (1)	setActive() IE5.5	onMouseEnter IE5.5
offsetHeight	setAttribute("attr",val[,case])	onMouseLeave IE5.5
offsetLeft	setCapture(container) W5	onMouseMove
offsetParent	setExpression("prop", "expr", "lang") W5	onMouseOver
offsetTop	swapNode(node) W5	onMouseUp
offsetWidth	tags("tag") (1)	onPaste W5
outerHTML	urns("URN") W5, (1)	onPropertyChange W5
outerText		onReadyStateChange
parentElement W4		onResize
parentTextEdit		onResizeEnd IE5.5
readyState		onResizeStart IE5.5
recordNumber W4		onSelectStart
runtimeStyle W5		
scopeName W5		
scrollHeight		
scrollLeft		
scrollTop		
scrollWidth		
sourceIndex		
style		
tabIndex		
tagName		
tagUrn W5		
title		
uniqueID W5		
(1) Property or method of all object collections		

popup W5.5		16
document	hide()	(None)
isOpen	show()	

FRAMESET		16
border	borderColor	
cols	frameBorder	
frameSpacing	rows	

FRAME		16
borderColor	Document	
frameBorder	height	
marginHeight	marginWidth	
noResize	scrolling	
src	width	

IFRAME		16
align	Document	
frameBorder	frameSpacing	
hspace	marginHeight	
marginWidth	scrolling	
src	vspace	

BASE		20
href	target	

BASEFONT		20
color	face	
size		

META		20
charset	content	
httpEquiv	name	
url		

TITLE		20
text		

document		18
activeElement	attachEvent("evt",func) IE5	onActivate IE5.5
alinkColor	clear()	onBeforeCut W5
all	clearAttributes() IE5	onBeforeDeactivate IE5.5
anchors[]	close()	onBeforeEditFocus W5
applet[]	createElement("tag")	onBeforePaste W5
bgColor	createEventObject() (ev) IE5.5	onClick
body	createStyleSheet("URL", [index])	onContextMenu W5
charset	detachEvent("evt",func) IE5	onControlSelect IE5.5
cookie	elementFromPoint(x,y)	onCut
defaultCharset	execCommand("cmd", [UI], [arg])	onDblClick
designMode W5	focus()	onDeactivate IE5.5
doctype	mergeAttributes(obj) W5	onDrag W5
domain	open(["mime"]Type, ["replace"])	onDragEnd W5
embed[]	queryCommandEnabled("cmd")	onDragEnter W5
expando	queryCommandIndeterm("cmd")	onDragLeave W5
fgColor	queryCommandState("cmd")	onDragOver W5
fileCreatedDate	queryCommandSupported("cmd")	onDragStart W5
fileModifiedDate	queryCommandText("cmd")	onDrop W5
fileSize	queryCommandValue("cmd")	onHelp W4, W5
forms[]	releaseCapture() IE5	onKeyDown
frames[]	setActive() IE5.5	onKeyPress
images[]	write("str")	onKeyUp
lastModified	write("str")	onMouseDown
linkColor		onMouseMove
location		onMouseOut
media IE5.5		onMouseOver
mimeTypes W5		onMouseUp
namespaces[] IE5.5		onPaste
parentWindow		onPropertyChange W5
plugins[]		onReadyStateChange
protocol		onResizeEnd IE5.5
readyState		onResizeStart IE5.5
referrer		onSelectionChange
security IE5.5		onStop IE5
selection		
styleSheets[]		
title		
uniqueID		
URL		
URLUnencoded IE5.5		
vlinkColor		

BODY		18
alink	createControlRange() W5	onAfterPrint W5
background	createTextRange()	onBeforePrint W5
bgColor	doScroll(["scrollAction"]) W5	onScroll
bgProperties		
bottomMargin		
leftMargin		
link		
noWrap		
rightMargin		
scrollLeft		
scrollTop		
text		
topMargin		
vLink		

JSB4

FORM		23
action	reset()	onReset
autocomplete ^{W5}	submit()	onSubmit
elements[]		
encoding		
enctype		
length		
method		
name		
target		

LABEL	23
htmlFor	(None)

BUTTON		24
INPUT (button, reset, submit, radio, checkbox)		
(See original object model button, reset, submit, radio, and checkbox object listings.)		

INPUT (image)		24
complete	(None)	
form		
name		
src		
type		

INPUT (text, password, hidden)		25
(See original object model text, password, and hidden object listings.)		
maxLength	onAfterUpdate ^{W4}	
readOnly	onBeforeUpdate ^{W4}	
size	onErrorUpdate ^{W4}	

TEXTAREA		25
(See original object model textarea object listing.)		
cols	createTextRange()	
readOnly	onAfterUpdate ^{W4}	
rows	onBeforeUpdate ^{W4}	
wrap	onErrorUpdate ^{W4}	

SELECT		26
(See original object model select object listing.)		
length	options[i].add(elem[, index])	(None)
multiple	options[i].remove()	
size		
value		

OPTION		26
defaultSelected	(None)	
form		
selected		
text		
value		

A (anchor/link)		21
hash		
host		
hostname		
href		
Methods		
contentType		
name		
nameProp		
pathname		
port		
protocol		
protocolLong		
rel		
rev		
search		
target		
urn		

IE4+ DHTML DOM Compatibility Guide

The baseline browser for this section is MSIE 4. An item with no notation is compatible back to that level for all OS versions. Notations as follows:

W4 — IE4+/Windows only

W5 — IE5+/Windows only

IE5 — IE5+ all OSes

IE5.5 — IE5.5+ (only Win tested)

M5 — IE5+/Mac

All HTML element objects share items from "All HTML" box on Page 1. "(None)" means no special methods or events for the current object.

IMG		22
align	(None)	
alt		
border		
complete		
dynsrc		
fileCreatedDate		
fileModifiedDate		
fileSize		
fileUpdatedDate		
height		
href		
hspace		
isMap		
loop		
lowsrc		
name		
nameProp ^{W5}		
protocol		
src		
start		
useMap		
vspace		
width		

AREA		22
alt	(None)	
coords		
hash		
host		
hostname		
href		
noHref		
pathname		
port		
protocol		
search		
shape		
target		

MAP		22
areas[]	(None)	
name		onScroll

MARQUEE		19
behavior	start()	onBounce
bgColor	stop()	onFinish
direction		onStart
height		
hspace		
loop		
scrollAmount		
scrollDelay		
trueSpeed		
vspace		
width		

OL		27
compact		
start		
type		

UL		27
compact		
type		

LI		27
type		
value		

DL, DT, DD, DIR, MENU	
compact	

TABLE		27
align	createCaption()	onScroll
background	createTFoot()	
bgColor	createTHead()	
border	deleteCaption()	
borderColor	deleteRow()	
borderColorDark	deleteTFoot()	
borderColorLight	deleteTHead()	
caption	deleteTHead() W5	
cellPadding	firstPage() W5	
cellSpacing	insertRow()	
cells	lastPage() W5	
cols	moveRow(<i>srcIndex</i> , <i>destIndex</i>) W5	
datePageSize	nextPage() W4	
frame	previousPage() W4	
height	refresh()	
rows		
rules		
tBodies		
tFoot		
tHead		
width		

TBODY, TFOOT, THEAD		27
align	deleteRow(<i>i</i>)	(None)
bgColor	insertRow(<i>i</i>)	
rows	moveRow(<i>srcIndex</i> , <i>destIndex</i>)	
vAlign		

TR		27
align	deleteCell(<i>i</i>)	(None)
bgColor	insertCell(<i>i</i>)	
borderColor		
borderColorDark		
borderColorLight		
cells		
height		
rowIndex		
sectionRowIndex		
vAlign		

TD, TH		27
align		
background		
bgColor		
borderColor		
borderColorDark		
borderColorLight		
cellIndex		
colSpan		
height		
noWrap		
rowSpan		
vAlign		
width		

CAPTION		27
align		
vAlign		

H1..H6		19
align		

HR		19
align		
color		
noShade		
size		
width		

BR		19
clear		

FONT		19
color		
face		
size		

TextRange W4		19
boundingHeight	collapse(<i>start</i>)	(None)
boundingLeft	compareEndPoints(<i>type</i> , <i>range</i>)	
boundingTop	duplicates()	
boundingWidth	execCommand(<i>cmd</i> [, <i>UI</i> , <i>val</i>])	
htmlText	expand(<i>unit</i>)	
offsetLeft	findText(<i>str</i> [, <i>scope</i> , <i>flags</i>])	
offsetTop	getBookmark()	
text	getBoundingClientRect()	
	getClientRects()	
	inRange(<i>range</i>)	
	isEqual(<i>range</i>)	
	move(<i>unit</i> [, <i>count</i>])	
	moveEnd(<i>unit</i> [, <i>count</i>])	
	moveStart(<i>unit</i> [, <i>count</i>])	
	moveToBookmark(<i>bookmark</i>)	
	moveToPoint(<i>x</i> , <i>y</i>)	
	parentElement()	
	pasteHTML(<i>HTMLText</i>)	
	queryCommandEnabled(<i>cmd</i>)	
	queryCommandIndeterm(<i>cmd</i>)	
	queryCommandState(<i>cmd</i>)	
	queryCommandSupported(<i>cmd</i>)	
	queryCommandText(<i>cmd</i>)	
	queryCommandValue(<i>cmd</i>)	
	scrollIntoView()	
	select()	
	setEndPoint(<i>type</i> , <i>range</i>)	

TextNode IE5		19
data	splitText(<i>offset</i>)	(None)
length		
nextSibling		
nodeName		
nodeType		
nodeValue		
parentNode		
previousSibling		

selection M4		19
type	clear()	(None)
	createRange()	
	empty()	

TextRectangle IE5		19
bottom		(None)
left		
right		
top		

IE4+ DHTML DOM Compatibility Guide

The baseline browser for this section is MSIE 4. An item with no notation is compatible back to that level for all OS versions. Notations as follows:
 W4 — IE4+/Windows only
 W5 — IE5+/Windows only
 IE5 — IE5+ all OSes
 IE5.5 — IE5.5+ (only Win tested)
 M5 — IE5+/Mac
 All HTML element objects share items from "All HTML" box on Page 1.
 "(None)" means no special methods or events for the current object.
 This Quick Reference does not contain listings for Microsoft's separate XML DOM.

<p>STYLE 30</p> <p>(None)</p> <p>media type</p>	<p>STYLE 30</p> <p>(None)</p> <p>addImport("URL",[index]) addRule("selector","styleSpec",[index]) removeRule(index)</p> <p>cssText IE5 disabled href id imports[] media owningElement pages[] IE5.5 parentStyleSheet readOnly rules[] title type</p>
<p>currentStyle IE5, runtimeStyle IE5.5</p> <p>(See style object)</p>	<p>currentStyle IE5, runtimeStyle IE5.5</p> <p>(See style object)</p>
<p>rule</p> <p>(None)</p> <p>readOnly selectorText style</p>	<p>rule</p> <p>(None)</p> <p>readOnly selectorText style</p>
<p>LINK 20</p> <p>(None)</p> <p>disabled href hreflang media rel rev styleSheet target type</p>	<p>LINK 20</p> <p>(None)</p> <p>disabled href hreflang media rel rev styleSheet target type</p>
<p>SCRIPT 20</p> <p>(None)</p> <p>defer event htmlFor language src text type</p>	<p>SCRIPT 20</p> <p>(None)</p> <p>defer event htmlFor language src text type</p>

<p>event 29</p> <p>altKey altLeft IE5.5 behaviorCookie W5.5 behaviorPart W5.5 bookmarks W4 boundElements button cancelBubble clientX clientY contentOverflow ctrlKey ctrlLeft IE5.5 dataFld W4 dataTransfer W5 fromElement keyCode W5.5 nextPage W5.5 offsetX offsetY propertyName W5 qualifier W4 reason W4 recordset W4 repeat W5 returnValue saveType W5.5 screenX screenY shiftKey shiftLeft IE5.5 srcElement srcFilter W4 srcUrn W5 toElement type x y</p>
--

<p>APPLET 32</p> <p>(None)</p> <p>align allHTML code codeBase height hspace name vspace width</p> <p>onCellChange W5 onDataAvailable W5 onDataSetChanged W5 onDataSetComplete W5 onLoad onRowEnter W5 onRowExit W5 onRowsDelete W5 onRowsInserted W5 onScroll</p>
--

<p>OBJECT 32</p> <p>(None)</p> <p>align allHTML BaseHref classid code codeBase codeType height hspace name object type vspace width</p> <p>onCellChange W5 onDataAvailable W5 onDataSetChanged W5 onDataSetComplete W5 onLoad onRowEnter W5 onRowExit W5 onRowsDelete W5 onRowsInserted W5 onScroll</p>
--

<p>EMBED 32</p> <p>(None)</p> <p>align height hidden name pluginspage src units width</p> <p>onLoad onScroll</p>

<p>XML W5 32</p> <p>(None)</p> <p>src XMLDocument</p> <p>(None)</p>
--