

Original DOM (NN2+, IE3+) Quick Reference — Page 1 of 2

window		16
<ul style="list-style-type: none"> _content N6 attachEvent("evt", func) IE5 back() N4 blur() N3, IE4 captureEvents(type) N4-Only clearInterval() N4, IE4 clearTimeout() N4 close() confirm("msg") createPopup() IE5.5 detachEvent("evt", func) IE5 disableExternalCapture() N4-Only enableExternalCapture() N4-Only execScript("expr", lang) IE4 find(["str"], case, bkwrd) N4-Only fireEvent("evt", [evObj]) IE5.5 focus() N3, IE4 forward() N4 handleEvent(event) N4-Only home() N4 moveBy(Δx, Δy) N4, IE4 moveTo(x, y) N4, IE4 navigate() IE3 open(URL, name, "specs") N4, IE4 print() N4, IE5 prompt("msg", "reply") releaseEvents(type) N4-Only resizeBy(Δx, Δy) N4, IE4 resizeTo(width, height) N4, IE4 routeEvent(event) N4-Only scroll(x, y) N3, IE4 scrollBy(Δx, Δy) N4, IE4 scrollTo(x, y) N4, IE4 setActive() IE5.5 setInterval(func, msec, [args]) N4, IE4, (2) setTimeout(func, msec, [args]) (2) showHelp() W4 showModalDialog() W4 stop() N4 	<ul style="list-style-type: none"> onAbort N6 onAfterPrint W5 onBeforePrint W5 onBlur N3, IE4 onBeforeUnload IE4 onBlur N3, IE4 onChange N6 onClick N6 onClose N6 onDragDrop N4, (S) onError N3, IE4 onFocus N3, IE4 onHelp IE4 onKeyDown N6 onKeyPress N6 onKeyUp N6 onLoad onMouseDown N6 onMouseMove N6 onMouseOut N6 onMouseOver N6 onMove N4-Only onReset N4, IE4 onScroll IE4 onSelect N6 onSubmit N6 onUnload 	
<ul style="list-style-type: none"> background bgColor clipBottom clipHeight clipLeft clipRight clipTop clipWidth document left name pageX pageY parentLayer siblingAbove siblingBelow src top visibility zIndex 	<ul style="list-style-type: none"> above background below bgColor clipBottom clipHeight clipLeft clipRight clipTop clipWidth document left name pageX pageY parentLayer siblingAbove siblingBelow src top visibility zIndex 	

(1) New window spaces for all browsers: height, width, toolbar, location, directories, status, menubar, scrollbars, resizable, copyHistory. Addr1 spaces for N4+ always opened(S), alwaysRaised(S), dependent, hotkeys, innerHeight, innerWidth, outerHeight, outerWidth, screenX, toolbar(S), z-index(S). Addr2 spaces for IE4+ channelmode, fullscreen, left, top. Addr3 space for IE5+ title.

(2) Optional args parameter added to N4, 3rd parameter in IE4 is for scripting language.

document		18
<ul style="list-style-type: none"> alinkColor anchors[] applets[] N3, IE4 bgColor cookie domain N3, IE4 embeds[] N3, IE4 fgColor forms[] height N3, IE4 images[] N3, IE4 lastModified layers[] N4-Only linkColor links[] location (1) referrer title URL N3, IE4 vlinkColor width N4 	<ul style="list-style-type: none"> captureEvents(type) N4-Only clear() close() getSelection() N4, (2) handleEvent(event) N4-Only open("mime/type", [replace]) (3) releaseEvents(type) N4-Only routeEvent(event) N4-Only write("string") writeln("string") 	

(1) Replaced by the URL property in Navigator 3.
 (2) N4 has a document.selection property to retrieve the currently selected text.
 (3) mime/type parameter new in N4, but only "text/html" type supported.

link ()		21
<ul style="list-style-type: none"> hash host hostname href pathname port protocol search target text N4 x N4 y N4 	<ul style="list-style-type: none"> onClick onDbClick N4, (1), IE4 onMouseDown N4, IE4 onMouseOut N4, IE4 onMouseOver onMouseUp N4, IE4 	

anchor ()		21
<ul style="list-style-type: none"> name N4, IE4 text N4 x N4 y N4 	<ul style="list-style-type: none"> (None) 	

image N3, (1), IE4		22
<ul style="list-style-type: none"> border complete height hspace lowsrc name src vspace width x N4 y N4 	<ul style="list-style-type: none"> onAbort onError onLoad 	

area N3, IE4		22
<ul style="list-style-type: none"> hash host hostname href pathname port protocol search target 	<ul style="list-style-type: none"> onClick N4 onMouseOut onMouseOver 	

history		17
<ul style="list-style-type: none"> length current(S), (1) next(S), (1) previous(S), (1) 	<ul style="list-style-type: none"> back() forward() go(int "URL") 	

(1) Accessible in NN3 via a security technique no longer in use. Available in NN4+ with signed scripts.

© 2001 Danny Goodman (www.dannyg.com). All Rights Reserved.
JSB4

form		23
action	handleEvent(evt) ^{N4}	onReset ^{N3, IE4}
elements[]	reset() ^{N3, IE4}	onSubmit
encoding	submit()	
length		
method		
name		
target		

button, reset, submit		24
checked	click()	onClick
form	handleEvent(evt) ^{N3}	onMouseDown ^{N4, IE4}
name		onMouseUp ^{N4, IE4}
type ^{N3, IE4}		
value		

checkbox		24
checked	click()	onClick
defaultChecked	handleEvent(evt) ^{N3}	onMouseDown ^{N4, IE4}
form		onMouseUp ^{N4, IE4}
name		
type ^{N3, IE4}		
value		

radio		24
checked	click()	onClick
defaultChecked	handleEvent(evt) ^{N3}	onMouseDown ^{N4, IE4}
form		onMouseUp ^{N4, IE4}
length		
name		
type ^{N3, IE4}		
value		

text, textarea, password, hidden		25
defaultValue (1)	blur()	onBlur
form	focus()	onChange
name	handleEvent(evt) ^{N4}	onFocus
type ^{N3, IE4}	select()	onKeyDown ^{N4, IE4}
value (2)		onKeyPress ^{N4, IE4}
		onKeyUp ^{N4, IE4}
		onSelect
(1) Not available for textarea object.		
(2) Password value property returns empty string in NN2.		

file input control		26
form	blur()	onBlur
name	focus()	onFocus
type	handleEvent(evt) ^{N4}	onSelect
value	select()	
(1) Netscape also calls this the fileUpload object.		

select		26
length	blur() ^{N3, IE4}	onBlur
name	focus() ^{N3, IE4}	onChange
options[]	handleEvent(evt) ^{N4}	onFocus
options[] . defaultSelected		
options[] . index		
options[] . selected		
options[] . text		
options[] . value		
selectedIndex		
type ^{N3, IE4}		

navigator		28
appName	javaEnabled() ^{N3, M4}	
appMinorVersion	preference(name, val) ^{N4, (S)}	
appName	taintEnabled() ^{N3, M4}	
appVersion		
browserLanguage		
cookieEnabled		
cpuClass		
language		
mimeType[]		
onLine		
platform		
plugins		
product		
productSub		
securityPolicy		
systemLanguage		
userAgent		
userLanguage		
userProfile		
vendor		
vendorSub		

mimeType		28
description	(None)	
enabledPlugin		
type		
suffixes		

plugin		28
name		
filename		
description		
length		
refresh()		

Screen		28
availHeight	(None)	
availLeft	(1)	
availTop	(1)	
availWidth		
bufferDepth	(2)	
colorDepth		
fontSmoothingEnabled	(2)	
height		
pixelDepth		
updateInterval	(2)	
width		
	(1)N4+ only.	
	(2)IE4+ only.	

Original DOM Compatibility Guide

Baseline browsers for this section are NN2, IE3/J1, and IE 3.01/Mac. An item with no notation is compatible back to that level. Notations indicate the browser and version in which the property, method, or event handler was introduced. An item showing to be introduced only in IE, for example, does not exist for any NN version.

Except for the window and navigator objects (whose listings cover all browsers and versions), new features listed in this section cover only through NN4 (and IE4 when they matched a new NN4 feature). Notations are as follows:

N3 — New in NN3
N4 — New in NN4
J2 — New in IE3, JScript.dll ver. 2

IE4 — New in IE4, all OSes

(S) — Requires signed scripts (NN)
Additional window and navigator object notations are:

W4 — IE4+/Windows only

W5 — IE5+/Windows only

IE5.5 — IE5.5+ (only Win tested)

M4 — IE4+/Mac only

M5 — IE5+/Mac only

N6 — New in NN6

Except for items marked N4-Only (which are not carried over into NN6), an item listed for an early browser is also available in the IE4+ and/or W3C DOM object models.

“(None)” means that no methods or events exist for the current object through IE3 and NN4.